

Corelink Sliding Enclosure – Rodent Proof

The CoreLink Rodent Proof sliding enclosures feature a slide out tray with 4 cable entry points to suit 20mm and 25mm glands. Enclosures come standard with a sliding cable entry bracket.

These enclosures are available in a host of configurations and connector variants with a broad range of adapter plates in both flat and angled, versatile cassette mounting and excellent cable management internally & for entering cables, all combine to offer a tailored solution for your needs.

This enclosure employs either a pair of rotating cable entry brackets or can be configured with a larger angled entry to allow for a range of cable entry configurations.

Applications:

- Splicing of tight buffered or loose-tube cable
- Direct termination of fibre optic cable including quick connects or epoxy field termination
- Installation of glanded pre-terminated cable assemblies
- Patching preterminated cable assemblies

Features and Benefits:




- Rugged powder coated steel construction ensures product durability
- Flat rodent proof cable entry with knockouts offers excellent protection of terminations even in challenging environments
- Range of panel and faceplate options to suit a broad variety of fibre types and adaptor styles
- Compact size offers excellent versatility even in shallow cabinets and racks
- Multiple cable entry locations helps ensure the enclosure is suitable for a Left or Right of incoming cable variations
- Adjustable mounting ears allow for a variety of rack positioning options from the front.
- S009:2013 compliant laser warning badge on all enclosures




Technical Specifications

Part Number	FX-R1R-1A1C-2C-0P
Description	CoreLink+ 1RU 2 Panel Sliding Enclosure Rodent Proof
Ratings & Dimensions	
Size WxHxD (mm)	485 x 44 x 255
Weight unit (kg)	3.25
Material and colour	Charcoal grey powdercoated - Rugged 1.2, 1.6 & 2.0mm steel construction
Adapter panel capacity	2 Flat or Angled
Port capacity (fibre count)	24
Splice capacity	48
Standard cable entry ports	2 x 20mm, 2 x 25mm slots

Inclusions

Part Number	Description	Appearance
FIBTRAY200-2L	1 x 12/24 Fibre Stackable Splice Cassette with Lid	
Standard Accessories	1x Spiral Gland - M20, 1x Strength Member Anchor 4x Cable ties 1x Pair of Rack mounting ears with screws 4x Cage Nuts 1x Velcro Loop 4 x Cable Management Clips	
FPP-SC12-AL	12 Port SC/LCD angled left panel - printed 1, 12	
FPP-SC12-AR	12 Port SC/LCD angled right panel - printed 1, 12	

Panel Options

Part Number	Description	
FPP-SC12-FL	2 x 12 Port SC/LCD Flat Panel – Printed 1,12 (13,24 on rear)	
Blank Panels		
FPP-BLANK	Blank Panel	