

JETTING
By fibre blowers. For fibre blowers.



Meet the Family Jetting Air Blown Machines



TrigAir – will blow 0.8 to 3mm cable into 3, 5, 7 and 8mm ducts for about 40-50m with no air and up to 500m with Air.



V0 – will blow 0.8 to 6mm cable into 3 to 16mm ducts for about 40-50m with no air and up to 1000m with Air.

Jetlogger installation optional tool available



DARE TO DO IT DIFFERENTLY.



V0-HD – will blow 0.8 to 6.5mm cable into 3 to 16mm ducts for about 40-50m with no air and up to 1000m with Air.

Jetlogger installation optional tool available



V2 – will blow 2.4 to 16mm cable into 7 to 50mm ducts for about 40-50m with no air and 1500-2500m with Air.

Joystick controller - is a feature of the V2 and V3 controlling both the forward and reverse deployment of the installation.

Jetlogger installation optional tool available



Meet the Family Jetting Air Blown Machines



V3 - will blow 4 to 40mm cable into 10 and 63mm ducts for about 40-50m with no air and 2500-3500m with Air.

Joystick controller - is a feature of the V2 and V3 controlling both the forward and reverse deployment of the installation.

Jetlogger installation optional tool available

Options

- **TrigAir:** A tripod is available for this product
- **Y Block:** For blowing a second and third cable.
- **After Blower for V3:** Handheld fibre blowing unit for small spaces.

Jetlogger installation

optional tool – for V0, V0-HD, V2 and V3 machines.

- It can describe the job, cable and pipe/duct.
- Automatically records temperature, humidity and the exact position by GPS.
- Monitors air-pressure, speed, distance and push force every minute.
- Will automatically shutdown the blowing machine if optimal pushing force is exceeded.
- All this data is shown live on the logger screen and can be produced as a PDF report



DARE TO DO IT DIFFERENTLY.