

## Optical Power Meter

- 2.5mm universal interface  $\pm 0.2$  dB accuracy
- Wavelengths 850-1625nm
- 0.01 dB Resolution
- Measurement Range -70~ +10dBm
- Manual calibration
- Waterproof keys suitable for various outdoor environments
- Silicone jacket, anti-drop 2m
- Equipped with LED light, not afraid of the dark



## Specifications

<b>Model</b>	KPM-35	<b>Accuracy</b>	$\pm 0.2$ db
<b>Wavelength</b>	800-1700nm	<b>Display Resolution</b>	0.01db
<b>Connector Type</b>	SC/FC/ST	<b>Operating Temperature</b>	-10~60°C
<b>Probe Type</b>	ingaAs	<b>Storage Temperature</b>	-25~70°C
<b>Measuring Range</b>	-70~+10db	<b>Power Supply</b>	3*AA 1.5V
<b>Dimension</b>	160*85*45mm	<b>Net Weight</b>	220g

## Optical Light Source

- 2.5mm universal interface + SC Adaptor
- Typical output power: -5dB
- Wavelengths : 850nm-1550nm
- Drop proof: 2m
- Low power function display
- Waterproof key suitable for all kinds of outdoor environments
- Silicon shell protection design: shock proof & drop proof
- LED backlight
- PON wavelengths 1310nm/1490nm/1550nm
- Plug and Play



## Specifications

<b>Model</b>	KLS-35/MS
<b>Wavelength</b>	850/1300/1310/1550nm
<b>Connector Type</b>	SC+2.5mm Universal
<b>Power Supply</b>	3*AA 1.5V
<b>Output Stability</b>	±0.05db/15mins, ±0.1db/8 hours
<b>Frequency</b>	CW,270Hz,1KHz,2KHz
<b>Dimension/Weight</b>	160*85*45mm/220g