

High Definition Core Aligning
fusion splicer

TYPE-72C+

Powered by



NanoTune™
Enhanced splice experience



SumiCloud™




Dependable

Splicing 5s/Heating 8s/Splice loss 0.01dB



Preventive
Maintenance



Dual speed
high heating



Proven field
toughness



Long life
battery

Specifications

Items	TYPE-72C+	
Optical fibre requirements	Material	Silica glass
	Fibre count / Profile types	Single / SMF(G.652), MMF(G.651), DSF(G.653), NZDSF(G.655), BIF(G.657), CSF(G.654), EDF
	Fibre diameter	Cladding diameter :80 ~150µm, Coating diameter :100 ~1,000µm
	Cleave length	5 ~16mm with coating clamp
Standard performance	Splice loss (typical)*1	SMF :0.01dB, MMF :0.01dB, DSF :0.03dB, NZDSF :0.03dB
	Return loss (typical)	60dB or greater
	Splice time (typical)	5sec(SM G652 Quick Mode), 7sec(SM G652 Std. Mode), 7sec(Auto Mode)
	Heating time (typical)	8sec (FPS-61-2.6 sleeve, S60mm 0.25 Quick Mode)
	Splice & Heat cycles per battery full charge*2	Approx. 320 (BU-16)
	Fibre view & magnification	2 CMOS cameras observation, 380X (zoom : 760X) for X or Y single axis view, 270X for both X & Y dual axis view
	Proof test	1.96 ~2.09N
Programs	Applicable protection sleeve	60mm, 40mm & Sumitomo Nano sleeves
	Splice programs	Max. 300, 74 are pre-optimised, 226 editable by user
Functions	Heating programs	Max. 100, 27 are pre-optimised, 73 editable by user
	Splice image capture / Splice data storage	200 images / 10,000 splice data (internal memory only) 50,200/20,000 (with 8GB SD card)
	Attenuation splicing	0.1dB to 15dB in 0.1dB increments
	Universal clamps	Provided, 200µm, 900µm tight & loose bu"er fibre
	Reversible coating clamps	Provided
	Dual automatic independent ovens	Provided
	User-selectable oven clamp operation	Provided
	Onboard user training video	Provided
	Automatic fibre identification	SMF / MMF / DSF / NZDSF / BIF / Other
	Automatic arc calibration	Automatically compensates for environmental condition changes
	Display of remaining Splice & Heat cycles	Provided (Battery mode)
Size / Weight	Wireless LAN connectivity (Option)*3	Provided
	Size	128(W) x 154(D) x 130(H) mm (without anti-shock rubber)
Terminals	Weight	1.9kg (without Battery) / 2.2kg (with Battery BU-16)
	Monitor	5.0" touch screen color LCD display
Power supply	DC output	DC 12V (for JR-6+)
	USB port	USB 2.0 (mini-B type)
Operating condition	Storage media	SD / SDHC memory card MAX32GB
	AC input	AC 100 ~240V, 50/60Hz (ADC-16)
Storage condition	DC input	DC 10 ~15V
	Battery pack	Li-ion 10.8V, 6,400mAh (BU-16)
Electrode life *4	Altitude :0 ~6,000m, Temperature :-10 ~+50°C, Humidity :0 ~95% (non-condensing), Wind velocity :up to 15m/sec	
Software updates	Temperature :-40 ~+80°C, Humidity :0 ~95% (non-condensing), Battery :-20 ~+30°C (long term)	
Data management	Internet	
		Can be stored, edited and analysed by dedicated PC software

*1 : Average value of the final inspection in room temperature with Sumitomo identical fibre. Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Wireless LAN connectivity is not available in all countries. For more details, please refer to our Web site. <https://global-sei.com/sumitomo-electric-splicers/products/sumicloud/>

*4 : Achieved in lab condition. Electrode life may vary depending on the operating environment.

Environmental Durability*

Shock resistance	Test details
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Impact resistance	Equivalent to IK07 on LCD monitor (Protected against 2J impact, it is equivalent to a 500g force from 40cm)
Water resistance	Equivalent to IPx2 (Operates normally after being exposed to water dripping at 3mm/min. for at least 2.5 min on each of 4 surfaces tilted at 15°)
Dust resistance	Equivalent to IP5X (Operates normally after 8 hours in a test chamber with circulating dust particles smaller than 75µm)

*Splicer operation after shock, impact, water or dust tests, was confirmed under battery power, by Sumitomo.
Does not guarantee the product will not be damaged by these conditions.

Basic Accessories

Part name	Part No.	Qty.
AC adapter	ADC-16 series	1pc
AC power cord	PC-AC<X>*	1pc
Cooling tray	—	1pc
Spare electrode	ER-10	1pair
Quick reference guide	—	1pc
Carrying case with worktable	CC-72	1pc
Hand strap	—	1pc
USB cable	—	1pc

*X=2(USA), 3(EU), 4(JP), 5(UK), 6(AUS), 7(South Africa)

Items listed in Basic Accessories are always included with the splicer body. Overall kit content may vary regionally. Please check with your local authorised reseller to confirm kit content in your region.

Accessories

	Part name	Part No.	Remarks
Accessories for Splicer	SumiCloud card	WLS-D series	For SumiCloud™ connection
	Fibre holder	FHS-025	For \$0.25mm single fibre
		FHS-09	For \$0.9mm single fibre
		FHS-025/LB5	For 0.9mm loose bu"ered single fibre
		FHD-1	For drop/indoor cable (Cable size : typical 2.0x3.1or2.6mm)
		1SM-ST	For indoor cable (Cable size : typical 1.6x2.0mm)
	Battery pack	FHC-3	For 3mm cable
	Battery charger	BU-16	Li-ion 6,400mAh
	Car battery cable	BC-16	—
	V-groove cleaning brush	PCV-16	For car battery operation (cigarette socket type)
Electrode	VGT-2	Brush for cleaning V-groove	
Accessories	Handheld fibre cleaver	ER-10	—
		FC-8R-FC	Automatic blade rotation cleaver with cleave counter
	Fibre cleaver	FC-8R-F	Automatic blade rotation cleaver
		FC-6S-C	Table-top high precision cleaver
	Jacket remover	FC-6RS-C	Automatic blade rotation cleaver
	Loose tube cutter	JR-M03	Jacket remover for single fibre
	Alcohol dispenser	LTC-01	—
	Fibre protection sleeve	HR-3	—
		FPS-1	60mm, diameter after shrink approx. \$3.2mm
		FPS-40	40mm, diameter after shrink approx. \$3.2mm
	FPS-61-2.6	61mm, diameter after shrink approx. \$2.6mm	



Carrying case with worktable
CC-72



Handy cleaver
FC-8R series



Table-top cleaver
FC-6 / FC-6R series



Jacket remover
JR-M03



Compatible with
Lynx-CustomFit™
Splice-on Connector



Electrode
ER-10

Ordering Information:

Part: SEI-T72C-PLUS

Description: Sumitomo Type-72C PLUS Standard Package Kit

Please contact atg for more detail and delivery times

Designed in Japan
072C+01-EMEA-EN001 (2020.05)
(TP)